# PA NT COOPERATION TREAT

·	From the INTERNATIONAL BUREAU
PCT	То:
NOTIFICATION OF ELECTION	Assistant Commissioner for Patents
	United States Patent and Trademark
(PCT Rule 61.2)	Office Box PCT
	Washington, D.C.20231
	ETATS-UNIS D'AMERIQUE
Date of mailing (day/month/year)	in its capacity as elected Office
22 May 2000 (22.05.00)	
International application No.	Applicant's or agent's file reference
PCT/GB99/03496	98P4851/F21518
International filing date (day/month/year)	Priority date (day/month/year)
27 October 1999 (27.10.99)	27 October 1998 (27.10.98)
Applicant	
HULBERT, Anthony, Peter	
The designated Office is hereby notified of its election mad	le:
	·
X in the demand filed with the International Preliminar	y Examining Authority on:
16 March 200	0 (16.03.00)
in a notice effecting later election filed with the Inter	national Bureau on:
	<u></u>
·	,
2. The election X was	
was not	
made before the expiration of 19 months from the priority	date or, where Rule 32 applies, within the time limit under
Rule 32.2(b).	
·	
	·
•	

Authorized officer

Pascal Piriou

The International Bureau of WIPO 34, chemin des Colombettes

1211 Geneva 20, Switzerland

### **PCT**







#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:
H04B 7/005

A1

(11) International Publication Number: WO 00/25444

(43) International Publication Date: 4 May 2000 (04.05.00)

(21) International Application Number: PCT/GB99/03496

(22) International Filing Date: 27 October 1999 (27.10.99)

(30) Priority Data:
9823396.8 27 October 1998 (27.10.98) GB

(71) Applicant (for all designated States except US): ROKE MANOR RESEARCH LIMITED [GB/GB]; Roke Manor, Old Salisbury Lane, Romsey, Hants SO51 0ZN (GB).

(72) Inventor: and

(75) Inventor/Applicant (for US only): HULBERT, Anthony, Peter [GB/GB]; 48 Wilton Crescent, Shirley, Southampton, Hants SO15 7QH (GB).

(74) Agent: KAY, Ross, Marcel; Siemens Shared Services Limited, Intellectual Property Department, Siemens House, Oldbury, Bracknell, Berkshire RG12 8FZ (GB). (81) Designated States: CN, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

**Published** 


With international search report.



(54) Title: METHOD OF AND APPARATUS FOR POWER CONTROL

#### (57) Abstract

When transmitting bursty data, for example packet data, a mobile terminal uses information relating to signal strength at the base station to determine the power at which the mobile terminal must transmit in order to produce a required signal to noise ratio at the base station. In frequency division duplex techniques, multi-path fading on the down-link is uncorrelated with multi-path fading on the up-link. Power measurements can be averaged at the mobile terminal over a likely fading period. However, this does not cater for instantaneous power level fluctuations in the up-link direction, which can result in the power transmitted by the mobile terminal being too high or too low at the start of a frame. The invention maintains a predetermined signal to noise ratio. At a given time slot, a power level is determined which, over remaining time slots, is based on the sum of power levels corresponding to previous time slots and the number of time slots remaining in the frame. Where multi-path fading occurs, smaller variations in average power over the frame will occur leading to improved system capacity.



#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Аттеліа	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA.	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan ·	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	ТJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary_	ML	Mali	TT	Trinidad and Tobago
ВJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JР	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PĻ	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## METHOD OF AND APPARATUS FOR POWER CONTROL

The present invention relates to a method of and apparatus for power control, of the type used in a communication system, for example, in a spread-spectrum communication system, such as a Code Division Multiple Access (CDMA) communication system.

In a CDMA cellular communication system, power control is used to equalize signal to noise (S/N) ratios of the signals received at a base station from various mobile terminals. In the term 'signal to noise ratio', the term 'noise' is intended to include interference in the form of signals from other mobile terminals, as well as background noise.

A known technique involves measuring the S/N ratio in respect of signals received from a given mobile terminal over a measurement interval and comparing the measured S/N ratio against a desired threshold. If the measured S/N ratio exceeds the desired threshold, a binary 1 (or 0, depending upon the convention employed) is transmitted (within the plurality of signals transmitted from the base station) to the mobile terminal originating the given signal. If the measured S/N ratio is lower than the desired threshold, a binary 0 (or 1, depending upon the convention employed) is transmitted to the given mobile terminal. The mobile terminal, in turn, responds by reducing its transmission power by, for example, 1 dB if a 1 (or 0) is received or by increasing its power by 1 dB if a 0 (or 1) is received. In this way, the received S/N ratio is held approximately constant as path loss between the given mobile station and the base station varies and/or as the level of interference at the base station from other mobile terminals varies.

The above technique is effective in the transmission of continuous data where any transients associated with the initial setting of transmitter power at

the mobile terminal can be ignored. However, where individual bursts (frames) of data are transmitted, for example packet data, the mobile terminal must set its initial transmitter power according to a so-called open loop power control technique. In this technique, the base station signals to the mobile terminal(s) the power at which the base station is transmitting; this can be either the total power received or the power of a particular signal which the mobile(s) station is receiving, and the interference level at the base station. The mobile terminal measures the power level of the corresponding signal received from the base station and uses the signalled information, i.e. the information relating to signal strength at the base station, to determine the power at which the mobile terminal must transmit in order to produce a required S/N ratio at the base station. On average, this should be the correct power. However, in many CDMA systems the frequency used for transmission from the base station to the mobile terminal (down-link) is different from the frequency used for transmission from the mobile terminal to the base station (up-link). Such a scheme is known as a Frequency Division Duplex (FDD) technique. In an FDD technique, propagation of signals is non-reciprocal in the short term, for example, multipath fading on the down-link is uncorrelated with multi-path fading on the uplink. This effect can be mitigated somewhat by averaging the power measurements at the mobile terminal over the likely fading period. However, this does not cater for the instantaneous path level fluctuations in the up-link direction, resulting in the power transmitted by the mobile terminal being too high or too low at the start of the frame.

In a typical CDMA system, Forward Error Correction (FEC) with interleaving is employed in order to mitigate the effects of fading and interference from other signals operating on the same frequency. If a known soft decision decoding technique is employed, the effect of the interleaving is to

make the probability of uncorrectable errors in an interleaved frame a function more of the average S/N ratio over the frame rather than, for example, the worst case S/N ratio. Consequently, if the S/N ratio at the start of a frame is too high, implementation of power control reduces the S/N ratio to the required threshold by the end of the frame, but the overall average will be higher than necessary. Conversely, if the S/N ratio at the start of a frame is too low, implementation of power control increases the S/N ratio to the required threshold by the end of the frame, but the overall average will be lower than necessary.

It is therefore an object of the present invention to obviate or at least mitigate the above described disadvantages.

According to the present invention, there is provided a method of power control in a communications system capable of transmitting a frame having a plurality of time intervals, the method comprising the steps of: selecting a time interval in respect of which a power level is to be determined; summing any previously measured power levels in respect of any time intervals preceding the selected time interval; determining the number of any remaining time intervals, and setting the power level in respect of the selected time interval based upon the sum of previously measured power levels and the number of remaining intervals in order to achieve a predetermined S/N ratio in respect of the frame.

Preferably, the power level is set during transmission of the frame in such a way as to tend to keep the received signal to noise averaged over the frame constant.

Thus, if the signal is received at a S/N ratio higher than necessary at the beginning of a frame, the method will ensure that the signal will be received at a level lower than the nominal S/N ratio by the end of the frame. Where multipath fading occurs the use of this method will result in smaller variation in average power over the frame, leading to an improvement in system capacity.

This differs from known techniques which try to modify the power level within each time interval so as to substantially keep to the predetermined signal to noise ratio during each interval.

Preferably, the time interval is a time slot.

At least one embodiment of the invention will now be described by way of example, with reference to the accompanying drawings, in which:

FIGURE 1 is a schematic diagram of the entities used in a communications system,

FIGURE 2 is a schematic diagram of a frame used by the system of Figure 1, and

FIGURE 3 is a flowchart of a method constituting an embodiment of the present invention.

Referring to Figure 1, a CDMA system comprises at least one base station 102 supporting a cell 104, the base station 102 being arranged to communicate with a mobile terminal 106 over a radio-frequency (RF) interface 108 by transmitting a frame 200 of data (Figure 2). The frame 200 comprises N time slots ts<sub>0</sub>, ..., ts<sub>N-1</sub>.

In operation, the frame 200 is transmitted from the mobile terminal 106 to the base station 102, during which power control is achieved by N adjustments of power corresponding to N time slots in the frame 200.

Referring to Figure 3, a required average S/N ratio  $\gamma_d$  at the base station 102 over the duration of the frame 200 is initially determined and set (step 300). A power level is then set so that the average S/N ratio  $\gamma_d$  per time slot at the base station 102 will be substantially met (step 300).

A subsequent time slot,  $ts_j$ , for which the power level is to be adjusted, is then selected (step 302) and the number of any remaining time slots, N-j, is determined (step 304). If the number of time slots remaining, N-j, is zero, no

further power levels are set for the frame 200 (step 306). If, however, one or more time slots remain, the sum of respective measured power levels received at the base station 102 during previous time slots is calculated (step 308). The calculation can be generally expressed as:  $\sum_{i=0}^{j-1} \gamma_i$ , where  $\gamma_i$  is the S/N ratio received in the *i*th slot.

Using the sum of the measured power levels, the predetermined average S/N ratio  $\gamma_d$  and knowledge of the number of remaining time slots, a predicted S/N ratio,  $\gamma_p$  is then calculated (step 310) and the value of  $\gamma_p$  is used to calculate the power level at which the mobile terminal 106 transmits signals to the base station 102. The equation used to calculate the predicted S/N ratio  $\gamma_p$  is derived as follows.

The predicted S/N ratio  $\gamma_p$  is calculated based upon the assumption that a target, of the average S/N ratio,  $\gamma_d$ , across the frame 200, will be met if the calculated predicted S/N ratio  $\gamma_p$  is maintained throughout the remainder of the frame 200, thereby keeping the average S/N ratio  $\gamma_d$  substantially constant over the frame 200.

Since N-j power control intervals (time slots) remain in the frame 200 for which a power level is to be predicted, in order to satisfy the S/N ratio requirement of N $\gamma_d$  for the entire frame 200, the predicted S/N ratio  $\gamma_p$  for the remaining intervals,  $\gamma_p$  needs to satisfy the following equation:

$$\sum_{i=0}^{j-1} \gamma_i + (N-j)\gamma_p = N\gamma_d$$

Thus, the above equation is solved for  $\gamma_p$  and hence the predicted required power level (and therefore the next threshold) is calculated using the following equation:

$$\gamma_p = \frac{N\gamma_d - \sum_{i=0}^{j-1} \gamma_i}{N - i}$$

During the selected time slot,  $ts_j$ , the mobile terminal 106 transmits at the power level set (step 312) corresponding to the associated predicted S/N ratio  $\gamma_P$ .

A subsequent time slot is then selected (step 302) and the above-described procedure for calculating and setting power levels is repeated (steps 304 to 312).

Minor obvious modifications can be made within the normal ability of a skilled person to take account of non zero periods for measurement and for signalling within the power control sub-system.

#### Claims:

1. A method of power control in a communications system capable of transmitting a frame having a plurality of time intervals, the method comprising the steps of:

selecting a time interval in respect of which a power level is to be determined;

summing any previously measured power levels in respect of any time intervals preceding the selected time interval;

determining the number of any remaining time intervals; and setting the power level in respect of the selected time interval based upon the sum of previously measured power levels and the number of remaining intervals so as to achieve a predetermined signal to noise ratio in respect of the frame.

- 2. A method according to Claim 1, wherein the power level setting step takes place during transmission of the frame.
- 3. A method according to Claim 1, wherein the power level setting step keeps the received signal to noise ratio averaged over the frame substantially constant.
- 4. A method according to Claim 1, wherein the time interval is a time slot.
- 5. A method according to Claim 1, wherein the communications system is a spread spectrum communications system.

- 6. A method according to Claim 5, wherein the spread spectrum communications system is a CDMA communications system.
- 7. A method according to Claim 6, wherein the power level setting step achieves a signal to noise ratio,  $\gamma_p$ , which is given by the formula:

$$\gamma_p = \frac{N\gamma_d - \sum_{i=0}^{j-1} \gamma_i}{N - j}$$

wherein  $\gamma_i$  is the S/N ratio received at the base station in the *i*th interval;  $\sum_{i=0}^{j-1} \gamma_i$  is the sum of S/N ratios received corresponding to previous time intervals; and  $N\gamma_d$  is the desired total S/N ratio sum over the frame.

8. A method substantially as hereinbefore described with reference to Figure3.






Fig. 2





**SUBSTITUTE SHEET (RULE 26)** 

<u> </u>			717 40 997 03490			
A. CLASS IPC 7	HO4B7/005					
According t	o International Patent Classification (IPC) or to both national classific	cation and IPC				
	SEARCHED					
IPC /	ocumentation searched (classification system followed by classificat H04B					
	tion searched other than minimum documentation to the extent that					
Electronic d	lata base consulted during the international search (name of data ba	ase and, where practical, sear	ch terms used)			
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT					
Category °	Citation of document, with indication, where appropriate, of the re	levant passages	Relevant to claim No.			
			The state of the s			
А	US 5 305 468 A (BRUCKERT EUGENE 19 April 1994 (1994-04-19) abstract column 3, line 29 -column 5, line claims 1-3 figures 5-7		1,8			
A	WO 97 17769 A (MARTIN PAUL MAXWEI INT LTD (GB); GOODINGS RUPERT LES 15 May 1997 (1997-05-15) page 1, line 13 -page 4, line 19 claims 1,2	LL ;IONICA SLIE A)	1,8			
	-	-/				
X Furth	ner documents are listed in the continuation of box C.	X Patent family memb	ers are listed in annex.			
* Special cat	tegories of cited documents :	"T" later document published	after the international filing date			
conside	ent defining the general state of the art which is not ered to be of particular relevance locument but published on or after the international ate	or priority date and not in cited to understand the priorition  "X" document of particular religious."	or conflict with the application but brinciple or theory underlying the evance; the claimed invention			
citation	"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "C" document which may throw doubts on priority claim(s) or involve an inventive step when the document is taken alone document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the					
P" docume	neans  nt published prior to the international filing date but an the priority date claimed	ments, such combined we ments, such combination in the art.  "&" document member of the	vith one or more other such docu- n being obvious to a person skilled same patent family			
Date of the a	actual completion of the international search	Date of mailing of the inte	ernational search report			
17	7 December 1999	12/01/2000				
Name and m	nailing address of the ISA  European Patent Office, P.B. 5818 Patentlaan 2  NL – 2280 HV Rijswijk  Tel. (+31–70) 340–2040, Tx. 31 651 epo nl, Fax: (+31–70) 340–3016	Authorized officer  Gkeli M				

1

C.(Continue	tion) DOCUMENTS CONSIDERED TO BE RELEVANT	PC1/GB 99/03496
	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
		TOO STATE TO CLEAN NO.
	EP 0 810 743 A (NIPPON ELECTRIC CO) 3 December 1997 (1997-12-03) column 1, line 42 -column 2, line 29 column 4, line 14 - line 59 column 6, line 46 -column 8, line 6 claim 1 figures 1-3	1,8

1

...formatio. patent family members

PCT/GB 99/03496

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
US 5305468 A	19-04-1994	CA 2088720 A,C KR 9608955 B	19-09-1993 10-07-1996	
WO 9717769 A	15-05-1997	AU 7501696 A BR 9611481 A EP 0860058 A	29-05-1997 02-02-1999 26-08-1998	
EP 0810743 A	03-12-1997	JP 2785804 B JP 9321699 A AU 2368697 A CA 2206365 A CN 1167411 A	13-08-1998 12-12-1997 04-12-1997 30-11-1997 10-12-1997	

Form PCT/ISA/210 (patent family annex) (July 1992)



International application No. PCT/GB99/03496

		the description,	pages:						
		the claims,	Nos.:						
		the drawings,	sheets:						
5.	×	This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):							
		(Any replacement si report.) see separate sheet	heet containing such amendments must be referred to under item 1 and annexed to this						
6.		litional observations, separate sheet	if necessary:						
III.	Nor	n-establishment of c	ppinion with regard to novelty, inventive step and industrial applicability						
1.		The questions whether the claimed invention appears to be novel, to involve an inventive step (to be non- obvious), or to be industrially applicable have not been examined in respect of:							
		the entire internation	nal application.						
	×	claims Nos. 8.							
be	caus	se:							
	oude		•						
			al application, or the said claims Nos. relate to the following subject matter which does national preliminary examination ( <i>specify</i> ):						
	×		ms or drawings ( <i>indicate particular elements below</i> ) or said claims Nos. 8 are so unclear opinion could be formed ( <i>specify</i> ):						
		the claims, or said c	laims Nos. are so inadequately supported by the description that no meaningful opinion						
		no international sea	rch report has been established for the said claims Nos						
2.	and		al preliminary examination report cannot be carried out due to the failure of the nucleotide noce listing to comply with the standard provided for in Annex C of the Administrative						
		the written form has	not been furnished or does not comply with the standard.						
		the computer readal	ble form has not been furnished or does not comply with the standard.						
			· · · · · · · · · · · · · · · · · · ·						
۷.			nder Article 35(2) with regard to novelty, inventive step or industrial applicability; ons supporting such statement						

WO 00/25444 PCT/GB99/03496

RMEL

Spee to

From the INTERNATIONAL BUREAU

PCT

NOTICE INFORMING THE APPLICANT OF THE **COMMUNICATION OF THE INTERNATIONAL** APPLICATION TO THE DESIGNATED OFFICES

(PCT Rule 47.1(c), first sentence)

KAY, Ross, Marcel Siemens Shared Services Limited Intellectual Property Department RECEIVED Siemens House

Oldbury, Bracknell

Berkshire RG12 8FZ **ROYAUME-UNI** 

12 MAY MAN

Date of mailing (day/month/year)

04 May 2000 (04.05.00)

Applicant's or agent's file reference 98P4851/F21518

International filing date (day/month/year)

Priority date (day/month/year)

IMPORTANT NOTICE

27 October 1998 (27.10.98)

International application No. PCT/GB99/03496

27 October 1999 (27.10.99)

Applicant

ROKE MANOR RESEARCH LIMITED et al

Notice is hereby given that the International Bureau has communicated, as provided in Article 20, the international application to the following designated Offices on the date indicated above as the date of mailing of this Notice: CN, JP, US

In accordance with Rule 47.1(c), third sentence, those Offices will accept the present Notice as conclusive evidence that the communication of the international application has duly taken place on the date of mailing indicated above and no copy of the international application is required to be furnished by the applicant to the designated Office(s).

The following designated Offices have waived the requirement for such a communication at this time:

The communication will be made to those Offices only upon their request. Furthermore, those/Offices do not require the applicant to furnish a copy of the international application (Rule 49.1(a-bis)).

3. Enclosed with this Notice is a copy of the international application as published by the International Bureau on 04 May 2000 (04.05.00) under No. WO 00/25444

#### REMINDER REGARDING CHAPTER II (Article 31(2)(a) and Rule 54.2)

If the applicant wishes to postpone entry into the national phase until 30 months (or later in some Offices) from the priority date, a demand for international preliminary examination must be filed with the competent International Preliminary Examining Authority before the expiration of 19 months from the priority date.

It is the applicant's sole responsibility to monitor the 19-month time limit.

Note that only an applicant who is a national or resident of a PCT Contracting State which is bound by Chapter II has the right to file a demand for international preliminary examination.

#### REMINDER REGARDING ENTRY INTO THE NATIONAL PHASE (Article 22 or 39(1))

If the applicant wishes to proceed with the international application in the national phase, he must, within 20 months or 30 months, or later in some Offices, perform the acts referred to therein before each designated or elected Office.

For further important information on the time limits and acts to be performed for entering the national phase, see the Annex to Form PCT/IB/301 (Notification of Receipt of Record Copy) and Volume II of the PCT Applicant's Guide.

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

J. Zahra

Telephone No. (41-22) 338.83.38

Facsimile No. (41-22) 740.14.35

3248048

#### PATENT COOPERATION TREATY





#### From the

INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To:

Kay, Ross Marcel.

SIEMENS SHARED SERVICE LIMITED

Intellectual Property Department

Siemens House

Oldbury

Bracknell

Berkshire RG12 8FZ GRANDE BRETAGNE RECEIVED

PCT

NOTIFICATION OF TRANSMITTAL OF THE INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Rule 71.1)

Date of mailing

(day/month/year)

22.12.2000

Applicant's or agent's file reference

F21518/98P4851

IIVIPUR

IMPORTANT NOTIFICATION

International application No. PCT/GB99/03496

International filing date (day/month/year)

27/10/1999

Priority date (day/month/year)

27/10/1998

Applicant

ROKE MANOR RESEARCH LIMITED et al.

- 1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
- 2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
- 3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

#### 4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/

**)**)

European Patent Office D-80298 Munich

Tet. +49 89 2399 - 0 Tx: 523656 epmu d

Fax: +49 89 2399 - 4465

Authorized officer

Pelatti, V

Tel.+49 89 2399-7309





# **PCT**

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's	or agent's file reference	FOR FURTUER ACT			ation of Transmittal of International
F21518/98P4851 FOR FURTHER A			TION	Preliminary	Examination Report (Form PCT/IPEA/416)
International	application No.	International filing date (da	ay/month/y	ear)	Priority date (day/month/year)
PCT/GB9	9/03496	27/10/1999			27/10/1998
Internationa H04B7/00	Patent Classification (IPC) or na 5	ational classification and IPC			
Applicant					
ROKE MA	ANOR RESEARCH LIMITE	ED et al.			
	ternational preliminary exam transmitted to the applicant a		orepared b	y this Inte	rnational Preliminary Examining Authority
2. This R	EPORT consists of a total of	7 sheets, including this	cover she	et.	
be (s		sis for this report and/or s 07 of the Administrative I	sheets cor	ntaining re	n, claims and/or drawings which have ctifications made before this Authority ee PCT).
3. This re	port contains indications rela	ating to the following item	ıs:		
1	Basis of the report				
<b>\$</b> }	☐ Priority	,			
133	☑ Non-establishment of control	ppinion with regard to nov	elty, inve	ntive step	and industrial applicability
IV	Lack of unity of invention				
V		nder Article 35(2) with re ons suporting such state		ovelty, inve	entive step or industrial applicability;
VI	Certain documents cit		÷		
.VII		nternational application			
VIII	△ Certain observations o	n the international applica	ation		
Date of subr	nission of the demand		Date of co	mpletion of	this report
16/03/200			22.12.200	0	
	nailing address of the international examining authority:	al	Authorized	dofficer	STATE OF STATE VALUE
<b>)</b>	European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d				(1334) (1344) (1344) (1344) (1344) (1344) (1344)

Telephone No. +49 89 2399 8947

Fax: +49 89 2399 - 4465

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB99/03496

#### I. Basis of the report

1.	res <sub>i</sub> the	response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments (Rules 70.16 and 70.17).):  Description, pages:							
	1,2	,4-6	as originally filed						
	3,3	a	with telefax of	16/10/2000					
	Cla	ims, No.:							
	1-1	1	with telefax of	16/10/2000					
	Dra	wings, sheets:							
	1/2,	2/2	as originally filed						
2.		With regard to the <b>language</b> , all the elements marked above were available or furnished to this Authority in the anguage in which the international application was filed, unless otherwise indicated under this item.							
	These elements were available or furnished to this Authority in the following language: , which is:								
	the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).								
		the language of po	ublication of the international	application (under Rule 48.3(b)).					
		the language of a 55.2 and/or 55.3).		purposes of international preliminary examination (under Rule					
3.	With regard to any <b>nucleotide and/or amino acid sequence</b> disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:								
		contained in the ir	nternational application in writ	ten form.					
		filed together with	the international application	n computer readable form.					
		furnished subsequ	uently to this Authority in writt	en form.					
		furnished subsequ	uently to this Authority in com	puter readable form.					
			at the subsequently furnished polication as filed has been f	written sequence listing does not go beyond the disclosure in urnished.					
		The statement that listing has been fu		computer readable form is identical to the written sequence					
4.	The	amendments have	e resulted in the cancellation	of:					



International application No. PCT/GB99/03496

1. Statement

Novelty (N)

Yes:

Claims 1-7

No:

Claims

Inventive step (IS)

Yes:

Claims 1-7

No:

Claims

Industrial applicability (IA)

Yes:

Claims 1-7

No:

Claims

2. Citations and explanations see separate sheet

## VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made: see separate sheet



#### Section I

Claim 1 has been greatly and unallowably broadened against original claim 1. 1).

Original claim 1 recited, in summary, the following steps;

- select a time interval,
- sum measured power levels for preceding intervals [in the frame],
- determine number of remaining intervals [in the frame],
- set power in selected interval based on preceding power levels and number of intervals remaining [in the frame] to achieve a predetermined [average] S/N ratio over the frame.

Apart from the clarification that information is passed from the transmitter to the receiver, new claim 1 is reduced to reciting that the receiver seeks to maintain an average S/N ratio across the frame. This wording encompasses a range of possibilities which was not directly and unambiguously foreseen by the original disclosure, and thus claim 1 infringes Article 34.2.(b) PCT.

It is noted that the penultimate paragraph on page 3 is not found to support new claim 1, since it has to be read in the context of the paragraph which precedes it.

Claims 2 and 11 also infringe Article 34.2.(b) PCT. 2).

In step i. it is recited merely that the initial transmission level is set. The only support for this step in the original disclosure appears to be in the second last paragraph of page 4 and in the flowchart of Fig. 3, box 300. Here it is stated that "a required average S/N ratio ... at the base station ... over the duration of the frame...is initially determined and set". Thus there is no support for a setting of the initial level to any arbitrary value as presently encompassed by claims 2 and 11.

In step ii. it is recited that the "cumulative SNR value over the received time interval of the frame" is determined. This is different from "summing any previously measured power levels [for each time interval]" (cf. original claim 1).

Summing the levels means adding together discrete values. Determining a cumulative value can encompass many more mathematical operations, including, for example, continuous integration which were not directly and unambiguously disclosed originally.

- Claim 3 is also not fully supported by the original disclosure. 3). The original disclosure stated that the predetermined average signal to noise ratio was that average S/N ratio at the base station over the duration of the frame (see description page 4, last full paragraph).
- 4). No original support at all can be found for new claim 9.
- In view of the fact that it would lead to a meaningless outcome if the present 5). claims were to be examined for novelty and inventive step in respect only of the features which are originally supported, this report is being established on the basis of the originally-filed claims.
- For similar reasons the adaptations to the description infringe Article 34(2)(b) and 6). are thus also ignored.

#### Section III

Claim 8: The scope of this claim is indeterminable. See PCT Guidelines III-4.10 1). and Rule 6.2(a) PCT.

#### Section V

- The invention relies on the insight that interleaving means that the probability of 1). uncorrectable errors in an interleaved frame is a function more of the average S/N ratio over the frame than the worst case S/N ratio.
- Essentially the invention resides in a method of power control wherein the 2). received power level in each preceding time interval (slot) is measured, and the power level is set in the current slot taking into account the sum of the someasured power levels and the number of remaining intervals (slots) in the

International application No. PCT/GB99/03496

current frame so as to achieve a predetermined average s/N ratio over the frame.

3). None of the available prior art discloses or hints at such a technique.

#### Section VIII

Claim 1 is considered, in principle, to relate to novel and inventive subject-matter. However, the claims are unclear (Article 6 PCT) in the following respects:

#### 1). Claim 1:

- a) It is not clear that the "time intervals preceding the selected time interval" are time intervals in the current frame.
- b) Similarly, it is not clear that the "number of any remaining time intervals" is the number remaining in the current frame.
- c) Similarly, it is not clear that the "sum of previously measured power levels" is the sum of measured power levels previously measured in the current frame.
- d) The expression "so as to achieve a predetermined signal to noise ratio <u>in</u> respect of the frame" is obscure. It should have been clarified that the predetermined signal to noise ratio is achieved averaged over the frame.

#### 2). Claim 2:

This claim casts doubt on the intended scope of claim 1. How can the power level be set other than during the transmission of the frame if, as stated in the last paragraph of claim 1, the power level for the "selected" time interval is set based inter alia on previously measured power levels [in the current frame]. It seems this claim should have been deleted.

#### 3). Claim 3:

It is unclear whether this is intended to specify that the average S/N is substantially constant from frame to frame or, in some manner, is constant during a single frame.

#### 4). Claim 8:

The scope of this claim is indeterminable. See PCT Guidelines III-4.10 and Rule 6.2(a) PCT. It should have been deleted.

A RESTANCES OF make the probability of uncorrectable errors in an interleaved frame a function more of the average S/N ratio over the frame rather than, for example, the worst case S/N ratio. Consequently, if the S/N ratio at the start of a frame is too high, implementation of power control reduces the S/N ratio to the required threshold by the end of the frame, but the overall average will be higher than necessary. Conversely, if the S/N ratio at the start of a frame is too low, implementation of power control increases the S/N ratio to the required threshold by the end of the frame, but the overall average will be lower than necessary.

It is therefore an object of the present invention to obviate or at least mitigate the above described disadvantages.

According to the present invention, there is provided a method of power control in a communications system capable of transmitting a frame having a plurality of time intervals, the method comprising the steps of: selecting a time interval in respect of which a power level is to be determined; summing any previously measured power levels in respect of any time intervals preceding the selected time interval; determining the number of any remaining time intervals, and setting the power level in respect of the selected time interval based upon the sum of previously measured power levels and the number of remaining intervals in order to achieve a predetermined S/N ratio in respect of the frame.

Preferably, the power level is set during transmission of the frame in such a way as to tend to keep the received signal to noise averaged over the frame constant.

Thus, if the signal is received at a S/N ratio higher than necessary at the beginning of a frame, the method will ensure that the signal will be received at a level lower than the nominal S/N ratio by the end of the frame. Where multipath fading occurs the use of this method will result in smaller variation in average power over the frame, leading to an improvement in system capacity.

7

#### Claims:

1. A method of power control in a communications system capable of transmitting a frame having a plurality of time intervals, the method comprising the steps of:

selecting a time interval in respect of which a power level is to be determined;

summing any previously measured power levels in respect of any time intervals preceding the selected time interval;

determining the number of any remaining time intervals; and setting the power level in respect of the selected time interval based upon the sum of previously measured power levels and the number of remaining intervals so as to achieve a predetermined signal to noise ratio in respect of the frame.

- 2. A method according to Claim 1, wherein the power level setting step takes place during transmission of the frame.
- 3. A method according to Claim 1, wherein the power level setting step keeps the received signal to noise ratio averaged over the frame substantially constant.
- 4. A method according to Claim 1, wherein the time interval is a time slot.
- 5. A method according to Claim 1, wherein the communications system is a spread spectrum communications system.

- 6. A method according to Claim 5, wherein the spread spectrum communications system is a CDMA communications system.
- 7. A method according to Claim 6, wherein the power level setting step achieves a signal to noise ratio,  $\gamma_p$ , which is given by the formula:

$$\gamma_{p} = \frac{N\gamma_{d} - \sum_{i=0}^{j-1} \gamma_{i}}{N - j}$$

wherein  $\gamma_i$  is the S/N ratio received at the base station in the *i*th interval;  $\sum_{i=0}^{j-1} \gamma_i$  is the sum of S/N ratios received corresponding to previous time intervals; and  $N\gamma_d$  is the desired total S/N ratio sum over the frame.

- 8. A method substantially as hereinbefore described with reference to Figure
- 3.

**PCT** 

REC'D 29 DEC 2000

WIPO

PCT

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's	or age	nt's file reference	FOR FURTHER ACTIO	See Notification of Transmittal of International
F21518/9	8P48	351	FOR FURTHER ACTIO	Preliminary Examination Report (Form PCT/IPEA/416)
Internationa	l appli	cation No.	International filing date (day/m	
PCT/GB9	9/03	496	27/10/1999	27/10/1998
Internationa H04B7/00		nt Classification (IPC) or nat	tional classification and IPC	,
Applicant				
ROKE M	ANO	R RESEARCH LIMITE	D et al.	
1. This ir and is	nterna trans	ational preliminary exami smitted to the applicant a	ination report has been prepared in the properties of the properti	pared by this International Preliminary Examining Authority
2. This F	REPO	RT consists of a total of	7 sheets, including this cover	ver sheet.
be (s	een a see R	mended and are the bas	sis for this report and/or shee 07 of the Administrative Instr	of the description, claims and/or drawings which have ets containing rectifications made before this Authority tructions under the PCT).
				•
3. This r		Basis of the report Priority Non-establishment of o Lack of unity of inventio Reasoned statement un citations and explanatio Certain documents citated	on nder Article 35(2) with regard ons suporting such statemen ed	
Date of sub	missio	on of the demand	Dat	ate of completion of this report
16/03/20	00		22.	2.12.2000
	exam Euro D-80 Tel.	g address of the international ining authority: opean Patent Office 0298 Munich +49 89 2399 - 0 Tx: 52365 : +49 89 2399 - 4465	Dr.	raper, A



International application No. PCT/GB99/03496

l. Basis	of the	report
----------	--------	--------

1.	This report has been drawn on the basis of (substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments (Rules 70.16 and 70.17).):  Description, pages:							
	1,2,	4-6	as originally filed					
	3,3	a	with telefax of	16/10/2000				
	Cla	ims, No.:						
	1-11		with telefax of	16/10/2000				
	Dra	wings, sheets:						
	1/2,	2/2	as originally filed					
2.	Witi lang	With regard to the <b>language</b> , all the elements marked above were available or furnished to this Authority in the anguage in which the international application was filed, unless otherwise indicated under this item.						
	These elements were available or furnished to this Authority in the following language: , which is:							
	the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).							
		the language of publication of the international application (under Rule 48.3(b)).						
		the language of a 55.2 and/or 55.3)		r the purposes of international preliminary examination (under Rule				
3.	With regard to any <b>nucleotide and/or amino acid sequence</b> disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:							
		contained in the i	nternational application	in written form.				
		filed together with	the international applic	ation in computer readable form.				
		furnished subseq	uently to this Authority in	n written form.				
		furnished subseq	uently to this Authority is	n computer readable form.				
			at the subsequently furn application as filed has t	nished written sequence listing does not go beyond the disclosure in seen furnished.				
		The statement the listing has been f		ded in computer readable form is identical to the written sequence				
4.	. The amendments have resulted in the cancellation of:							

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB99/03496

		the description,	pages:						
		the claims,	Nos.:						
		the drawings,	sheets:						
5.	×	This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):							
		(Any replacement sh report.) see separate sheet	neet containing such amendments must be referred to under item 1 and annexed to this						
6.		litional observations, i separate sheet	if necessary:						
<b>III</b> .	Nor	n-establishment of o	pinion with regard to novelty, inventive step and industrial applicability						
1.	The obv	The questions whether the claimed invention appears to be novel, to involve an inventive step (to be non-obvious), or to be industrially applicable have not been examined in respect of:							
		the entire international application.							
	×	claims Nos. 8.							
be	caus	se:							
			al application, or the said claims Nos. relate to the following subject matter which does national preliminary examination ( <i>specify</i> ):						
	×		ns or drawings ( <i>indicate particular elements below</i> ) or said claims Nos. 8 are so unclear opinion could be formed ( <i>specify</i> ):						
		the claims, or said c could be formed.	laims Nos. are so inadequately supported by the description that no meaningful opinion						
		no international sear	rch report has been established for the said claims Nos						
2.	and	A meaningful international preliminary examination report cannot be carried out due to the failure of the nucleotic and/or amino acid sequence listing to comply with the standard provided for in Annex C of the Administrative nstructions:							
		the written form has	not been furnished or does not comply with the standard.						
		the computer readal	ble form has not been furnished or does not comply with the standard.						
٧.	Rea	asoned statement ui	nder Article 35(2) with regard to novelty, inventive step or industrial applicability;						

citations and explanations supporting such statement



International application No. PCT/GB99/03496

1. Statement

Novelty (N)

Yes:

Claims 1-7

No:

Claims

Inventive step (IS)

Yes:

Claims 1-7 Claims

No:

- -


Industrial applicability (IA)

Yes: No: Claims 1-7 Claims

2. Citations and explanations see separate sheet

## VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made: see separate sheet



#### Section I

Claim 1 has been greatly and unallowably broadened against original claim 1. 1).

Original claim 1 recited, in summary, the following steps;

- select a time interval,
- sum measured power levels for preceding intervals [in the frame],
- determine number of remaining intervals [in the frame],
- set power in selected interval based on preceding power levels and number of intervals remaining [in the frame] to achieve a predetermined [average] S/N ratio over the frame.

Apart from the clarification that information is passed from the transmitter to the receiver, new claim 1 is reduced to reciting that the receiver seeks to maintain an average S/N ratio across the frame. This wording encompasses a range of possibilities which was not directly and unambiguously foreseen by the original disclosure, and thus claim 1 infringes Article 34.2.(b) PCT.

It is noted that the penultimate paragraph on page 3 is not found to support new claim 1, since it has to be read in the context of the paragraph which precedes it.

Claims 2 and 11 also infringe Article 34.2.(b) PCT. 2).

In step i. it is recited merely that the initial transmission level is set. The only support for this step in the original disclosure appears to be in the second last paragraph of page 4 and in the flowchart of Fig. 3, box 300. Here it is stated that "a required average S/N ratio...at the base station...over the duration of the frame...is initially determined and set" . Thus there is no support for a setting of the initial level to any arbitrary value as presently encompassed by claims 2 and 11.

In step ii. it is recited that the "cumulative SNR value over the received time interval of the frame" is determined. This is different from "summing any previously measured power levels [for each time interval]" (cf. original claim 1).

Summing the levels means adding together discrete values. Determining a cumulative value can encompass many more mathematical operations, including, for example, continuous integration which were not directly and unambiguously disclosed originally.

- Claim 3 is also not fully supported by the original disclosure. 3). The original disclosure stated that the predetermined average signal to noise ratio was that average S/N ratio at the base station over the duration of the frame (see description page 4, last full paragraph).
- No original support at all can be found for new claim 9. 4).
- In view of the fact that it would lead to a meaningless outcome if the present 5). claims were to be examined for novelty and inventive step in respect only of the features which are originally supported, this report is being established on the basis of the originally-filed claims.
- For similar reasons the adaptations to the description infringe Article 34(2)(b) and 6). are thus also ignored.

#### Section III

Claim 8: The scope of this claim is indeterminable. See PCT Guidelines III-4.10 1). and Rule 6.2(a) PCT.

#### Section V

- The invention relies on the insight that interleaving means that the probability of 1). uncorrectable errors in an interleaved frame is a function more of the average S/N ratio over the frame than the worst case S/N ratio.
- Essentially the invention resides in a method of power control wherein the 2). received power level in each preceding time interval (slot) is measured, and the power level is set in the current slot taking into account the sum of the someasured power levels and the number of remaining intervals (slots) in the

current frame so as to achieve a predetermined average s/N ratio over the frame.

None of the available prior art discloses or hints at such a technique. 3).

#### Section VIII

Claim 1 is considered, in principle, to relate to novel and inventive subject-matter. However, the claims are unclear (Article 6 PCT) in the following respects:

#### 1). Claim 1:

- a) It is not clear that the "time intervals preceding the selected time interval" are time intervals in the current frame.
- b) Similarly, it is not clear that the "number of any remaining time intervals" is the number remaining in the current frame.
- c) Similarly, it is not clear that the "sum of previously measured power levels" is the sum of measured power levels previously measured in the current frame.
- d) The expression "so as to achieve a predetermined signal to noise ratio in respect of the frame" is obscure. It should have been clarified that the predetermined signal to noise ratio is achieved averaged over the frame.

#### 2). Claim 2:

This claim casts doubt on the intended scope of claim 1. How can the power level be set other than during the transmission of the frame if, as stated in the last paragraph of claim 1, the power level for the "selected" time interval is set based inter alia on previously measured power levels [in the current frame]. It seems this claim should have been deleted.

#### 3). Claim 3:

It is unclear whether this is intended to specify that the average S/N is substantially constant from frame to frame or, in some manner, is constant during a single frame.

#### 4). Claim 8:

The scope of this claim is indeterminable. See PCT Guidelines III-4.10 and Rule 6.2(a) PCT. It should have been deleted.

#### Claims:

16-10-2000

- 1. A method of power control in a communications system capable of transmitting a frame having a plurality of time intervals from a transmitter to a receiver, wherein power control is effected on the individual time intervals based upon information passed from the receiver to the transmitter, wherein the receiver seeks to maintain an average signal to noise ratio across the frame.
- 2. A method according to claim 1, wherein the method comprises:
- i. for a first time interval of a frame, setting the initial transmission power level; and
  - ii. for each subsequent time interval of the frame:

measuring the received signal to noise ratio over subsequent time intervals:

determining the cumulative SNR value over the received time interval of the frame;

determining the number of time intervals remaining in the frame; and, adjusting the transmission power level in response to signalling from the receiver in respect of a further subsequent time interval based upon said cumulative SNR value and the number of time intervals remaining in the frame such that the required average signal to noise ratio is substantially achieved.

3. A method according to Claim 2, wherein the transmission power level for each subsequent slot is set by:

calculating a predicted signal to noise ratio  $\gamma_p$  using the sum of the measured power levels, the predetermined average S/N ratio  $\gamma_d$  and the number of remaining time slots.

- A method according to Claim 2, wherein the required signal to noise 4. ration  $\gamma_p$  is calculated based upon the assumption that a target, of the average signal to noise ratio,  $\gamma_d$ , across the frame, will be met if the calculated predicted signal to noise ratio  $\gamma_p$  is maintained throughout the remainder of the frame, thereby keeping the average signal to noise ratio  $\gamma_d$  substantially constant over the frame.
- 5. A method according to any one of Claims 1 to 4, wherein the time interval is a time slot.
- 6. A method according to any one of Claims 1 to 5, wherein the communications system is a spread spectrum communications system.
- 7. A method according to Claim 6, wherein the spread spectrum communications systems is a CDMA communications system.
- 8. A method according to Claim 4, wherein the power level setting step achieves a signal to noise ratio,  $\gamma_p$ , which is given by the formula:

$$\gamma_{p} = \frac{N\gamma_{d} - \sum_{i=0}^{j-1} \gamma_{i}}{N - j}$$

wherein  $\gamma_i$  is the S/N ratio received at the base station in the *i*th interval;  $\sum_{i=1}^{j-1} \gamma_i$  is the sum of S/N ratios received corresponding to previous time intervals; and Nya is the desired total S/N ratio sum over the frame.

- 9. A method according to Claim 6, wherein the duration of a frame corresponds to a burst comprising a plurality of consecutive CDMA frames.
- 10. A method according to Claim 6, wherein the duration of a frame corresponds to the duration of a CDMA frame.
- 11. A transmitter for a communication system operable to transmit in time frames having a plurality of time intervals, the transmitter comprising a power controller operable to:
- i. for a first time interval of a frame, set the initial transmission power level; and,
- ii. for each subsequent time interval of the frame:

  measure the received signal to noise ratio over subsequent time intervals;

  determine the cumulative SNR value over the received time interval of
  the frame;

determine the number of time intervals remaining in the frame; and, adjust the transmission power level in response to signalling from the receiver in respect of a further subsequent time interval based upon said cumulative SNR value and the number of time intervals remaining in the frame such that the required average signal to noise ratio is substantially achieved.

make the probability of uncorrectable errors in an interleaved frame a function more of the average S/N ratio over the frame rather than, for example, the worst case S/N ratio. Consequently, if the S/N ratio at the start of a frame is too high, implementation of power control reduces the S/N ratio to the required threshold by the end of the frame, but the overall average will be higher than necessary. Conversely, if the S/N ratio at the start of a frame is too low, implementation of power control increases the S/N ratio to the required threshold by the end of the frame, but the overall average will be lower than necessary.

It is therefore an object of the present invention to obviate or at least mitigate the above described disadvantages.

According to the present invention, there is provided a method of power

control in a communications system capable of transmitting a frame having a plurality of time intervals from a transmitter to a receiver, wherein power control is effected on the individual time intervals based upon information passed from the receiver to the transmitter, wherein the receiver seeks to maintain an average signal to noise ratio across the frame. In accordance with a further aspect of the invention, there is provided a method according to claim 1, wherein the method comprises: for a first time i. interval of a frame, setting the initial transmission power level; and for each subsequent time interval of the frame: measuring the received signal to noise ratio over subsequent time intervals; determining the cumulative SNR value over the received time interval of the frame; determining the number of time intervals remaining in the frame; and, adjusting the transmission power level in response to signalling from the receiver in respect of a further subsequent time interval based upon said cumulative SNR value and the number of time intervals remaining in the frame such that the required average signal to noise ratio is substantially achieved.

Thus, if the signal is received at a S/N ratio higher than necessary at the beginning of a frame, the method will ensure that the signal will be received at a level lower than the nominal S/N ratio by the end of the frame. Where multipath fading occurs the use of this method will result in smaller variation in average power over the frame, leading to an improvement in system capacity.

In accordance with another aspect of the invention, there is provided a transmitter for a communication system operable to transmit in time frames having a plurality of time intervals, the transmitter comprising a power controller operable to:

i. for a first time interval of a frame, set the initial transmission power level; and,


ii. for each subsequent time interval of the frame: measure the received signal to noise ratio over subsequent time intervals; determine the cumulative SNR value over the received time interval of the frame; determine the number of time intervals remaining in the frame; and, adjust the transmission power level in response to signalling from the receiver in respect of a further subsequent time interval based upon said cumulative SNR value and the number of time intervals remaining in the frame such that the required average signal to noise ratio is substantially achieved.





(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference	(Form PCT/IS/	n of Transmittal of International Search Report V220) as well as, where applicable, item 5 below.
98P4851/F21518	ACTION	-
International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)
PCT/GB 99/03496	27/10/1999	27/10/1998
Applicant		
ROKE MANOR RESEARCH LIMIT	ED et al.	
This International Search Report has been according to Article 18. A copy is being tra	n prepared by this International Searching A ansmitted to the International Bureau.	authority and is transmitted to the applicant
This International Search Report consists  X It is also accompanied by	of a total of sheets. a copy of each prior art document cited in t	his report.
Basis of the report		
<ul> <li>a. With regard to the language, the language in which it was filed, unl</li> </ul>	international search was carried out on the ess otherwise indicated under this item.	basis of the international application in the
the international search w Authority (Rule 23.1(b)).	as carried out on the basis of a translation of	of the international application furnished to this
b. With regard to any <b>nucleotide</b> an was carried out on the basis of th	d/or amino acid sequence disclosed in the e sequence listing:	e international application, the international search
I <u>—</u>	onal application in written form.	
	ernational application in computer readable t	form.
	this Authority in written form.	
	this Authority in computer readble form.	
international application a	osequently furnished written sequence listin is filed has been furnished.	
the statement that the info furnished	ormation recorded in computer readable for	m is identical to the written sequence listing has been
2. Certain claims were fou	nd unsearchable (See Box I).	
3. Unity of invention is lac	king (see Box II).	
4. With regard to the title,		
X the text is approved as su	ubmitted by the applicant.	
the text has been establis	shed by this Authority to read as follows:	
5. With regard to the abstract,		•
	ubmitted by the applicant.	and the second in Day III. The coefficient may
the text has been establis within one month from the	shed, according to Rule 38.2(b), by this Auth e date of mailing of this international search	nority as it appears in Box III. The applicant may, report, submit comments to this Authority.
6. The figure of the drawings to be pub	lished with the abstract is Figure No.	3
as suggested by the appl	icant.	None of the figures.
because the applicant fai	• •	
because this figure better	r characterizes the invention.	



			Pt 18 99/03496	
a. classii IPC 7	FICATION OF SUBJECT MATTER H04B7/005			
According to	b International Patent Classification (IPC) or to both national classifica	ition and IPC		
B. FIELDS	SEARCHED			
Minimum do IPC 7	cumentation searched (classification system followed by classification H04B	on symbols)		
	ion searched other than minimum documentation to the extent that su			
Electronic da	ata base consulted during the international search (name of data bas	e and, where practical	ı, search terms used)	
C. DOCUME	ENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the rele	evant passages	Relevant to claim No.	
Α	US 5 305 468 A (BRUCKERT EUGENE J 19 April 1994 (1994-04-19) abstract column 3, line 29 -column 5, line claims 1-3 figures 5-7		1,8	
Α	WO 97 17769 A (MARTIN PAUL MAXWEL INT LTD (GB); GOODINGS RUPERT LES 15 May 1997 (1997-05-15) page 1, line 13 -page 4, line 19 claims 1,2		1,8	
X Furth	ner documents are listed in the continuation of box C.	χ Patent family	members are listed in annex.	
"A" document defining the general state of the art which is not considered to be of particular relevance  "E" earlier document but published on or after the international filing date  "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other means  "P" document published prior to the international filing date but later than the priority date claimed  "E"		T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone  Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.  &" document member of the same patent family  Date of mailing of the international search report		
	actual completion of the international search 7 December 1999	12/01/2	·	
Name and n	mailing address of the ISA  European Patent Office, P.B. 5818 Patentlaan 2  NL – 2280 HV Rijswijk  Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  Fax: (+31-70) 340-3016	Authorized officer		

1



Intercapility and Application No. PC 8 99/03496

	tion) DOCUMENTS CONSIDERED TO BE RELEVANT	1		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
	EP 0 810 743 A (NIPPON ELECTRIC CO) 3 December 1997 (1997-12-03) column 1, line 42 -column 2, line 29 column 4, line 14 - line 59 column 6, line 46 -column 8, line 6 claim 1 figures 1-3	1,8		

1

Inform

pn patent family members

Interponal Application No
PC 8 99/03496

Patent document cited in search report		Publication date		atent family member(s)	Publication date
US 5305468	Α	19-04-1994	CA KR	2088720 A,C 9608955 B	19-09-1993 10-07-1996
WO 9717769	Α	15-05-1997	AU BR EP	7501696 A 9611481 A 0860058 A	29-05-1997 02-02-1999 26-08-1998
EP 0810743	Α	03-12-1997	JP JP AU CA CN	2785804 B 9321699 A 2368697 A 2206365 A 1167411 A	13-08-1998 12-12-1997 04-12-1997 30-11-1997 10-12-1997